

DUAL BAND DIPLEXER

1. Characteristics (at -40 ~+85°C)

Part Number	LFD182G45MJ6D922
-------------	------------------

<Low Band >

Pass Band Range	f1		2450.00 ± 50.00MHz
Insertion Loss(dB)	ANT-LB	in f1	0.60 max at 25°C 0.65 max at -40~ +85°C
Attenuation (dB)	ANT-LB	4800.00–4992.00	32.0 min.
		7200.00–7488.00	24.0 min.
VSWR	LB	in f1	1.80 max.
	ANT	in f1	1.80 max.

<High Band>


Pass Band Range	f2		5425.00 ± 525.00 MHz
Insertion Loss(dB)	ANT-HB	in f2	0.70 max at 25°C 0.80 max at -40~ +85°C
Attenuation (dB)	ANT-HB	30.00–2700.00	32.0 min.
		9800.00–11900.00	15.0 min.
		14700.00–17850.00	11.0 min.
VSWR	HB	in f2	1.80 max.
	ANT	in f2	1.80 max.

Isolation (dB)	LB-HB	30.00–2700.00	32.0 dB min.
		in f2	28.0 dB min.
Power Capacity			2 W max

LB : Low Band Port


HB : High Band Port

ANT : Common Port




M01 : S(1,3) Freq 2.400G Hz S(dB) -0.404	M07 : S(1,1) Freq 2.400G Hz S(dB) -25.081
M02 : S(1,3) Freq 2.500G Hz S(dB) -0.454	M08 : S(1,1) Freq 2.500G Hz S(dB) -22.475

M03 : S(1,3) Freq 4.800G Hz S(dB) -41.295
M04 : S(1,3) Freq 4.992G Hz S(dB) -45.728
M05 : S(1,3) Freq 7.200G Hz S(dB) -31.180
M06 : S(1,3) Freq 7.488G Hz S(dB) -33.187



M09 : S(2,3) Freq 4.900G Hz S(dB) -0.516	M17 : S(2,2) Freq 4.900G Hz S(dB) -18.257
M10 : S(2,3) Freq 5.950G Hz S(dB) -0.341	M18 : S(2,2) Freq 5.950G Hz S(dB) -23.342
M11 : S(2,3) Freq 5.000M Hz S(dB) -40.692	
M12 : S(2,3) Freq 2.700G Hz S(dB) -40.230	
M13 : S(2,3) Freq 9.800G Hz S(dB) -29.083	
M14 : S(2,3) Freq 11.900G Hz S(dB) -22.034	
M15 : S(2,3) Freq 14.700G Hz S(dB) -19.095	
M16 : S(2,3) Freq 17.850G Hz S(dB) -23.214	

2. Construction,Dimensions&Marking



Mark	Meaning
A	Directional Input Mark

(in mm)

Mark	Dimension	Mark	Dimension	Mark	Dimension
L	1.6 ± 0.1	a	0.2 ± 0.1	e	0.3 ± 0.1
W	0.8 ± 0.1	b	0.20 ± 0.15	p	0.50 ± 0.05
T	0.7 max.	c	0.15 ± 0.10	-	-

TERMINAL CONFIGURATION


Terminal No.	Terminal Name	Terminal No.	Terminal Name
(1)	GND	(4)	P1
(2)	P3	(5)	GND
(3)	GND	(6)	P2

P1 : Lower Frequency Port

P2 : Higher Frequency Port

P3 : Common Port

3. Land Pattern



- Land
- Solder resist
- No pattern
- Solder resist
- Through Hole $\phi 0.30$

*Line width to be designed to match 50 Ω characteristic impedance, depending on PCB material and thickness.

**PLEASE READ THIS NOTICE BEFORE USING OUR PRODUCTS.**

Please make sure that your product has been evaluated and confirmed from the aspect of the fitness for the specifications of our product when our product is mounted to your product.

All the items and parameters in this product specification/datasheet/catalog have been prescribed on the premise that our product is used for the purpose, under the condition and in the environment specified in this specification. You are requested not to use our product deviating from the condition and the environment specified in this specification.

Please note that the only warranty that we provide regarding the products is its conformance to the specifications provided herein. Accordingly, we shall not be responsible for any defects in products or equipment incorporating such products, which are caused under the conditions other than those specified in this specification.

WE HEREBY DISCLAIMS ALL OTHER WARRANTIES REGARDING THE PRODUCTS, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, THAT THEY ARE DEFECT-FREE, OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS.

The product shall not be used in any application listed below which requires especially high reliability for the prevention of such defect as may directly cause damage to the third party's life, body or property. You acknowledge and agree that, if you use our products in such applications, we will not be responsible for any failure to meet such requirements.

Furthermore, YOU AGREE TO INDEMNIFY AND DEFEND US AND OUR AFFILIATES AGAINST ALL CLAIMS, DAMAGES, COSTS, AND EXPENSES THAT MAY BE INCURRED, INCLUDING WITHOUT LIMITATION, ATTORNEY FEES AND COSTS, DUE TO THE USE OF OUR PRODUCTS IN SUCH APPLICATIONS.

- Aircraft equipment.
- Undersea equipment.
- Medical equipment.
- Traffic signal equipment.
- Burning / explosion control equipment
- Application of similar complexity and/ or reliability requirements to the applications listed in the above.
- Aerospace equipment
- Power plant control equipment
- Transportation equipment (vehicles, trains, ships, elevator, etc.).
- Disaster prevention / crime prevention equipment.

We expressly prohibit you from analyzing, breaking, Reverse-Engineering, remodeling altering, and reproducing our product. Our product cannot be used for the product which is prohibited from being manufactured, used, and sold by the regulations and laws in the world.

We do not warrant or represent that any license, either express or implied, is granted under any our patent right, copyright, mask work right, or our other intellectual property right relating to any combination, machine, or process in which our products or services are used. Information provided by us regarding third-party products or services does not constitute a license from us to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from us under our patents or other intellectual property.

Please do not use our products, our technical information and other data provided by us for the purpose of developing of mass-destruction weapons and the purpose of military use.

Moreover, you must comply with "foreign exchange and foreign trade law", the "U.S. export administration regulations", etc.

Please note that we may discontinue the manufacture of our products, due to reasons such as end of supply of materials and/or components from our suppliers.

Customer acknowledges that Murata will, if requested by you, conduct a failure analysis for defect or alleged defect of Products only at the level required for consumer grade Products, and thus such analysis may not always be available or be in accordance with your request (for example, in cases where the defect was caused by components in Products supplied to Murata from a third party).

By signing on specification sheet or approval sheet, you acknowledge that you are the legal representative for your company and that you understand and accept the validity of the contents herein.

When you are not able to return the signed version of specification sheet or approval sheet within 90 days from receiving date of specification sheet or approval sheet, it shall be deemed to be your consent on the content of specification sheet or approval sheet.

Customer acknowledges that engineering samples may deviate from specifications and may contain defects due to their development status.

We reject any liability or product warranty for engineering samples.

In particular we disclaim liability for damages caused by

- the use of the engineering sample other than for evaluation purposes, particularly the installation or integration in the product to be sold by you,
- deviation or lapse in function of engineering sample,
- improper use of engineering samples.

We disclaims any liability for consequential and incidental damages.

If you can't agree the above contents, you should inquire our sales.

All the technical data and Information contained herein are subject to change without prior notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Murata:](#)

[LFD182G45MJ6D922](#)