

40011000000 - 400 Series



Series: 400

Questions? [Contact Littelfuse Support](#)

[Fuse 400 Datasheet](#)

The Littelfuse 400 Series is a TE5® Time Lag Fuse with High Breaking Capacity.

Features:

- Operating temperature: -40°C to 125°C
- Higher nominal melting I²T
- Higher interrupt rating
- Broad current rating 500mA to 6.3A
- Lead-Free, Halogen-Free, Compliance with RoHS
- Shock safe casing

Applications:

- SMPS for NB, printers, adaptors, consumer electronics, industrial controllers, battery chargers

Check Stock

Order Samples

Feedback

Electrical Characteristics	Technical Resources	Environmental Info
Property (Mouseover for details)	Value	
Ampere Rating (A)	1	
Nominal Melting I²T (A²sec)	9.63	
Interrupting Rating	130A@250VAC	
Min Operating Temp °C	-40	
Max Operating Temp (°C)	85	
Nominal Power Dissipation (W)	432	
Nominal Voltage Drop (mV)	89	
Nominal Cold Resistance (Ohms)	0.0808	
Opening	Slo-Blo/Time Lag (T)/Time Delay	
Package Size	TE5 (8.5x8mm)	
VAC (V)	250	

Connect with Littelfuse

Sign up to receive special offers and news

For more details about how we use your information, check our [Privacy Statement](#).

Mobile Site

About Littelfuse

[About Littelfuse](#)

[Conflict Free Statement](#)

[History](#)

[Investor Relations](#)

[Legal](#)

[Press Room](#)

[Privacy Statement](#)

[Supply Chain Transparency](#)

[Website Feedback](#)

Explore Littelfuse

[Capabilities Brochures](#)

[Careers](#)

[Check Distributor Stock](#)

[Competitor Cross Reference](#)

[Industries](#)

[Order Samples](#)

[Products](#)

[Services](#)

Technical Resources

[Application Designs](#)

[Education](#)

[FAQs](#)

[iDesign™](#)

[Littelfuse University](#)

[Product Catalogs](#)

[Quality Documents](#)

[Technical Documents](#)