600mA, Ultra-Low Dropout, Ultra-Fast CMOS LDO Regulator

General Description

The RT9187B is a high-performance, 600mA LDO regulator, offering extremely high PSRR and ultra-low dropout. This chip is ideal for portable RF and wireless applications with demanding performance and space requirements.

A noise reduction pin is also available for further reduction of output noise. Regulator ground current increases only slightly in dropout, further prolonging the battery life. The RT9187B also works well with low-ESR ceramic capacitors, reducing the amount of board space necessary for power applications, critical in hand-held wireless devices.

The RT9187B consumes less than 0.1μA in shutdown mode and has fast turn-on time for less than 40μs. The other features include ultra-low dropout voltage, high output accuracy, current limiting protection, and high ripple rejection ratio. The RT9187B is available in the SOT-23-5 package.

Ordering Information

RT9187B□□

- Package Type
  B : SOT-23-5
- Lead Plating System
  G : Green (Halogen Free and Pb Free)

Note :

Richtek products are :

- RoHS compliant and compatible with the current requirements of IPC/JEDEC J-STD-020.
- Suitable for use in SnPb or Pb-free soldering processes.

Marking Information



04= : Product Code

DNN : Date Code

Features

- **Ultra-Low-Noise for RF Application**
- **Ultra-Fast Response in Line/Load Transient**
- **Quick Start-Up (Typically 40μs)**
- **<0.1μA Standby Current When Shutdown**
- **Low Dropout : 100mV at 500mA**
- **Wide Operating Voltage Ranges : 2.5V to 5.5V**
- **TTL-Logic-Controlled Shutdown Input**
- **Current Limiting Protection**
- **Thermal Shutdown Protection**
- **Only 2.2μF Output Capacitor Required for Stability**
- **High Power Supply Rejection Ratio**
- **RoHS Compliant and Halogen Free**

Applications

- CDMA/GSM Cellular Handsets
- Battery-Powered Equipment
- Laptop, Palmtops, Notebook Computers
- Hand-Held Instruments
- Mini PCI & PCI-Express Cards
- PCMCIA & New Cards
- Portable Information Appliances

Pin Configurations

(TOP VIEW)



SOT-23-5

Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Typical Application Circuit



$$V_{OUT} = 0.8 \times (1 + \frac{R1}{R2}) \text{ Volts}$$

Note : The value of R2 should be less than 80kΩ to maintain regulation.

Function Pin Description

Pin No.	Pin Name	Pin Function
1	VIN	Voltage Input.
2	GND	Ground.
3	EN	Chip Enable (Active High).
4	ADJ	Output Voltage Feedback.
5	VOUT	Voltage Output.

Function Block Diagram



Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Absolute Maximum Ratings (Note 1)

- Supply Input Voltage ---------- 6V
- EN Input Voltage ---------- 6V
- Power Dissipation, P_D @ T_A = 25°C
  SOT-23-5 ---------- 0.400W
- Package Thermal Resistance (Note 2)
  SOT-23-5, θ_{JA} ---------- 250°C/W
- Lead Temperature (Soldering, 10 sec.) ---------- 260°C
- Junction Temperature ---------- 150°C
- Storage Temperature Range ---------- –65°C to 150°C
- ESD Susceptibility (Note 3)
  HBM ---------- 2kV
  MM ---------- 200V

Recommended Operating Conditions (Note 4)

- Supply Input Voltage ---------- 2.5V to 5.5V
- EN Input Voltage ---------- 0V to 5.5V
- Junction Temperature Range ---------- –40°C to 125°C
- Ambient Temperature Range ---------- –40°C to 85°C

Electrical Characteristics

(V_{IN} = V_{OUT} + 1V, V_{EN} = V_{IN}, C_{IN} = C_{OUT} = 2.2µF (Ceramic), T_A = 25°C, unless otherwise specified)

Parameter		Symbol	Test Conditions	Min	Typ	Max	Unit
Reference Voltage Tolerance		V_{REF}		0.784	0.8	0.816	V
ADJ Pin Current		I_{ADJ}	V_{ADJ} = V_{REF}	--	10	100	nA
Quiescent Current (Note 5)		I_Q	$V_{EN} \geq V_{IH}$, I_{OUT} = 0mA	--	380	500	µA
Standby Current (Note 6)		I_{STBY}	$V_{EN} \leq V_{IL}$, V_{IN} = 3.3V	--	0.1	1	µA
Current Limit		I_{LIM}	R_{LOAD} = 0.5Ω, V_{IN} = 3.3V	2	--	--	A
Dropout Voltage (Note 7)		V_{DROP}	I_{OUT} = 0.3A, V_{OUT} = 5V	--	60	100	mV
			I_{OUT} = 0.5A, V_{OUT} = 5V	--	100	200	
Load Regulation (Note 8)		ΔV_{LOAD}	V_{IN} = (V_{OUT} + 0.5V) 10mA < I_{OUT} < 0.5A	--	0.4	--	%/A
EN Threshold Voltage	Logic-High	V_{IH}	V_{IN} = 3.3V	1.8	--	--	V
	Logic-Low	V_{IL}	V_{IN} = 3.3V	--	--	0.6	
Enable Pin Current		I_{EN}	V_{IN} = 3.3V, Enable	--	0.1	1	µA
Power Supply Rejection Rate	f = 100Hz	PSRR	I_{OUT} = 300mA	--	–60	--	dB
	f = 10kHz			--	–50	--	
Line Regulation		ΔV_{LINE}	V_{IN} = (V_{OUT} + 0.5) to 5.5V, I_{OUT} = 1mA	--	--	0.3	%
Start-Up Time		t_{Start_Up}	R_{LOAD} = 3Ω	--	40	--	µs
Thermal Shutdown Temperature		T_{SD}		--	170	--	°C
Thermal Shutdown Hysteresis		ΔT_{SD}		--	30	--	

Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Note 1. Stresses beyond those listed "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions may affect device reliability.

Note 2. θ_{JA} is measured at T_A = 25°C on a low effective thermal conductivity single-layer test board per JEDEC 51-3.

Note 3. Devices are ESD sensitive. Handling precaution is recommended.

Note 4. The device is not guaranteed to function outside its operating conditions.

Note 5. Quiescent, or ground current, is the difference between input and output currents. It is defined by $I_Q = I_{IN} - I_{OUT}$ under no load condition (I_{OUT} = 0mA). The total current drawn from the supply is the sum of the load current plus the ground pin current.

Note 6. Standby current is the input current drawn by a regulator when the output voltage is disabled by a shutdown signal (V_{EN} <0.6V).

Note 7. The dropout voltage is defined as $V_{IN} - V_{OUT}$, which is measured when V_{OUT} is $V_{OUT(NORMAL)}$ – 100mV.

Note 8. Regulation is measured at constant junction temperature by using a 2ms current pulse. Devices are tested for load regulation in the load range from 10mA to 0.5A.

Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Typical Operating Characteristics

(C_{OUT} = 2.2µF/x5R, unless otherwise specified)

Quiescent Current vs. Temperature



Quiescent Current vs. Input Voltage



Dropout Voltage vs. Load Current



Current Limit



EN Pin Shutdown Response



Start Up



Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Line Transient Response



Load Transient Response



PSRR



Region of Stable C_{OUT} ESR vs. Load Current



Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Applications Information

Output Voltage Setting

The voltage divider resistors can have values up to 80kΩ because of the very high impedance and low bias current of the sense comparator. The output voltage is set according to the following equation :

$$V_{OUT} = V_{REF} \times \left(1 + \frac{R1}{R2}\right)$$

where VREF is the reference voltage with a typical value of 0.8V.

Chip Enable Operation

The RT9187B goes into sleep mode when the EN pin is in a logic low condition. In this condition, the pass transistor, error amplifier, and band gap are all turned off, reducing the supply current to 1μA (max.). The EN pin can be directly tied to VIN to keep the part on.

C_{IN} and C_{OUT} Selection

Like any low dropout regulator, the external capacitors of the RT9187B must be carefully selected for regulator stability and performance. Using a capacitor of at least 2.2μF is suitable. The input capacitor must be located at a distance of not more than 0.5 inch from the input pin of the IC. Any good quality ceramic capacitor can be used. However, a capacitor with larger value and lower ESR (Equivalent Series Resistance) is recommended since it will provide better PSRR and line transient response. The RT9187B is designed specifically to work with low ESR ceramic output capacitor for space saving and performance consideration. Using a ceramic capacitor with value at least 2.2μF and ESR larger than 10mΩ on the RT9187B output ensures stability. Nevertheless, the RT9187B can still work well with other types of output capacitors due to its wide range of stable ESR. "Typical Operating Characteristics" shows the allowable ESR range as a function of load current for various output capacitance. Output capacitors with larger capacitance can reduce noise and improve load transient response, stability, and PSRR. The output capacitor should be located at a distance of not more than 0.5 inch from the output pin of the RT9187B.

Thermal Considerations

For continuous operation, do not exceed absolute maximum junction temperature. The maximum power dissipation depends on the thermal resistance of the IC package, PCB layout, rate of surrounding airflow, and difference between junction and ambient temperature. The maximum power dissipation can be calculated by the following formula :

$$P_{D(MAX)} = (T_{J(MAX)} - T_A) / \theta_{JA}$$

where $T_{J(MAX)}$ is the maximum junction temperature, T_A is the ambient temperature, and θ_{JA} is the junction to ambient thermal resistance.

For recommended operating condition specifications, the maximum junction temperature is 125°C. The junction to ambient thermal resistance, θ_{JA}, is layout dependent. For SOT-23-5 packages, the thermal resistance, θ_{JA}, is 250° C/W on a standard JEDEC 51-3 single-layer thermal test board. The maximum power dissipation at T_A = 25°C can be calculated by the following formula :

$P_{D(MAX)}$ = (125°C – 25°C) / (250°C/W) = 0.400W for SOT-23-5 package

The maximum power dissipation depends on the operating ambient temperature for fixed $T_{J(MAX)}$ and thermal resistance, θ_{JA}. The derating curve in Figure 1 allows the designer to see the effect of rising ambient temperature on the maximum power dissipation.



Figure 1. Derating Curve of Maximum Power Dissipation

Copyright ©2012 Richtek Technology Corporation. All rights reserved. RICHTEK is a registered trademark of Richtek Technology Corporation.

Outline Dimension



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.889	1.295	0.035	0.051
A1	0.000	0.152	0.000	0.006
B	1.397	1.803	0.055	0.071
b	0.356	0.559	0.014	0.022
C	2.591	2.997	0.102	0.118
D	2.692	3.099	0.106	0.122
e	0.838	1.041	0.033	0.041
H	0.080	0.254	0.003	0.010
L	0.300	0.610	0.012	0.024

SOT-23-5 Surface Mount Package

Richtek Technology Corporation

5F, No. 20, Taiyuen Street, Chupei City

Hsinchu, Taiwan, R.O.C.

Tel: (8863)5526789

Richtek products are sold by description only. Richtek reserves the right to change the circuitry and/or specifications without notice at any time. Customers should obtain the latest relevant information and data sheets before placing orders and should verify that such information is current and complete. Richtek cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Richtek product. Information furnished by Richtek is believed to be accurate and reliable. However, no responsibility is assumed by Richtek or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Richtek or its subsidiaries.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Richtek:
RT9187BGB