


# RMCF / RMCP Series

General Purpose Thick Film Standard Power and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions



## Features:

- RMCF – standard power ratings
- RMCP – high power ratings
- Nickel barrier terminations standard
- Power derating from 100% at 70°C to zero at +155°C
- RoHS compliant, REACH compliant, and halogen free
- AEC-Q200 compliant (except 01005 size)
- For ultra-high power, see [RMCP-UP Series – Thick Film Ultra High-Power Chip Resistor](#)

## Electrical Specifications - RMCF

Type/Code	Power Rating (W) @ 70°C	Max. Working Voltage (V) <sup>(1)</sup>	Max. Overload Voltage (V)	Jumper Rated Current (A)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance <sup>(2)</sup>	
						1%	5%
RMCF01005	0.03	15	30	0.5	± 300	10 - 97.6	
					± 200	100 - 1M	
RMCF0201	0.05	25	50	0.5	± 400	1 - 9.76	
					± 200	10 - 10M	
RMCF0402	0.063	50	100	1	± 200	1 - 9.76	
					± 100	10 - 1M	
					± 200	1.02M - 22.1M	1.1M - 22M
RMCF0603	0.1	75	150	1	± 500	0.1 - 0.499	
					± 400	0.5 - 0.976	
					± 200	1 - 9.76	1 - 9.1
					± 100	10 - 1M	10 - 10M
					± 200	1.02M - 22.1M	11M - 22M
RMCF0805	0.125	150	300	2	± 200	0.1 - 9.76	0.1 - 9.1
					± 100	10 - 1M	10 - 10M
					± 200	1.02M - 22.1M	
RMCF1206	0.25	200	400	2	± 200	0.1 - 9.76	0.1 - 9.1
					± 100	10 - 10M	
					± 200	10.2M - 22.1M	11M - 22M
RMCF1210	0.5	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 100	10 - 10M	
RMCF2010	0.75	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 200	-	10 - 10M
					± 100	10 - 10M	-
RMCF2512	1	200	400	3	± 200	0.1 - 0.976	
					± 400	1 - 9.76	
					± 200	-	10 - 10M
					± 100	10 - 10M	-

Notes: (1) Lesser of  $\sqrt{P \cdot R}$  or maximum working voltage

(2) Contact Stackpole for higher or lower values

# RMCF / RMCP Series

General Purpose Thick Film Standard Power  
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

## Electrical Specifications - RMCP

Type/Code	Power Rating (W) @ 70°C	Max. Working Voltage (V) <sup>(1)</sup>	Max. Overload Voltage (V)	Jumper Rated Current (A)	TCR (ppm/°C)	Ohmic Range (Ω) and Tolerance <sup>(2)</sup>
						1%, 5%
RMCP0201	0.063	25	50	1	-200 / +400	1 - 9.76
					± 200	10 - 10M
RMCP0402	0.125	50	100	1.5	± 200	1 - 9.76
					± 100	10 - 10M
RMCP0603	0.25	75	150	2	± 200	1 - 9.76
					± 100	10 - 10M
RMCP0805	0.33	150	300	2.5	± 200	1 - 9.76
					± 100	10 - 10M
RMCP1206	0.5	200	400	3.5	± 400	1 - 9.76
					± 100	10 - 10M
RMCP1210	0.66	200	400	5	± 400	1 - 9.76
					± 100	10 - 10M
RMCP2010	1	200	400	6	± 200	1 - 9.76
					± 100	10 - 10M
RMCP2512	2	250	500	7	± 200	1 - 9.76
					± 100	10 - 10M

Notes: (1) Lesser of  $\sqrt{P \cdot R}$  or maximum working voltage

(2) Contact Stackpole for higher or lower values

The resistance value range for RMCP jumper is max. 0.02Ω

## Electrical Specifications - RMCF Jumper

Type/Code	Jumper Rated Current (A)	Max Overload Current (A)*	Jumper Resistance Value (Ω)
RMCF01005	0.5	1	0.05 max.
RMCF0201	0.5	1	
RMCF0402	1	3	
RMCF0603	1	5	
RMCF0805	2	10	
RMCF1206	2	10	
RMCF1210	3	12	
RMCF2010	3	12	
RMCF2512	3	15	

\* < 1 second and 1 time


# RMCF / RMCP Series

General Purpose Thick Film Standard Power  
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

## Mechanical Specifications



Type/Code	Typical Unit Weight (mg)	L Body Length	W Body Width	H Body Height	a Top Termination	b Bottom Termination	Unit
RMCF01005	0.07	0.016 ± 0.001 0.40 ± 0.02	0.008 ± 0.001 0.20 ± 0.02	0.005 ± 0.001 0.13 ± 0.02	0.004 ± 0.001 0.10 ± 0.03	0.004 ± 0.001 0.10 ± 0.03	inches mm
RMCF0201 RMCP0201	0.16	0.024 ± 0.001 0.60 ± 0.03	0.012 ± 0.001 0.30 ± 0.03	0.009 ± 0.002 0.23 ± 0.05	0.006 ± 0.002 0.15 ± 0.05	0.006 ± 0.002 0.15 ± 0.05	inches mm
RMCF0402 RMCP0402	0.5 0.62	0.039 ± 0.004 1.00 ± 0.10	0.020 ± 0.002 0.50 ± 0.05	0.012 ± 0.004 0.30 ± 0.10	0.006 ± 0.004 0.15 ± 0.10	0.010 ± 0.006 0.25 ± 0.15	inches mm
RMCF0603 RMCP0603	1.9 2.0	0.061 ± 0.006 1.55 ± 0.15	0.031 ± 0.006 0.80 ± 0.15	0.018 ± 0.006 0.45 ± 0.15	0.012 ± 0.008 0.30 ± 0.20	0.012 ± 0.008 0.30 ± 0.20	inches mm
RMCF0805 RMCP0805	5.00 4.37	0.079 ± 0.008 2.00 ± 0.20	0.049 ± 0.004 1.25 ± 0.10	0.020 ± 0.006 0.50 ± 0.15	0.014 ± 0.010 0.35 ± 0.25	0.014 ± 0.010 0.35 ± 0.25	inches mm
RMCF1206 RMCP1206	8.9	0.126 ± 0.010 3.20 ± 0.25	0.063 ± 0.006 1.60 ± 0.15	0.022 ± 0.006 0.55 ± 0.15	0.020 ± 0.012 0.50 ± 0.30	0.020 ± 0.012 0.50 ± 0.30	inches mm
RMCF1210 RMCP1210	15.55 15.96	0.126 ± 0.010 3.20 ± 0.25	0.098 ± 0.010 2.50 ± 0.25	0.022 ± 0.006 0.55 ± 0.15	0.020 ± 0.012 0.50 ± 0.30	0.020 ± 0.012 0.50 ± 0.30	inches mm
RMCF2010 RMCP2010	23.6 24.2	0.197 ± 0.008 5.00 ± 0.20	0.098 ± 0.008 2.50 ± 0.20	0.022 ± 0.006 0.55 ± 0.15	0.024 ± 0.012 0.60 ± 0.30	0.024 ± 0.014 0.60 ± 0.35	inches mm
RMCF2512 RMCP2512	40.02 39.45	0.248 ± 0.008 6.30 ± 0.20	0.126 ± 0.010 3.20 ± 0.25	0.022 ± 0.008 0.55 ± 0.20	0.024 ± 0.012 0.60 ± 0.30	0.024 ± 0.014 0.60 ± 0.35	inches mm

## Performance Characteristics

Test	Test Specifications	Test Conditions (JIS-C 5202)
Short Time Overload	± (2% + 0.1Ω)	RCWV*2.5 or Max. Overload Voltage, whichever is lower for 5 seconds.
	Jumper: Max 0.05Ω after test	0201 = 1 A 0402 / 0603 = 2.5 A 0805 / 1206 / 1210 / 2010 / 2512 = 5 A
Dielectric Withstanding Voltage	No flashover or breakdown	100 VAC, 1 minute
Resistance to Soldering Heat	± 1%	260 ± 5°C, for 10 seconds ± 0.5 seconds (Solder Bath)
Solderability	95% coverage, minimum	235 ± 5°C, for 2 seconds ± 0.5 seconds (Colophonium flux)
Temperature Cycle	± (1% + 0.05Ω) Jumper (< 0.05Ω)	-65°C: 30 minutes 25°C: 2 to 3 minutes 155°C: 30 minutes 25°C: 2 to 3 minutes (5 Cycles)
Load Life (Endurance)	1% and below: ± (1% + 0.05Ω) 2% and 5%: ± (3% + 0.1Ω) Value < 1Ω: ± (3% + 0.1Ω) Jumper: Max 0.1Ω after test.	70 ± 2°C, RCWV or max. working voltage whichever is less for 1000 hours with 1.5 hours "ON" and 0.5 hour "OFF"
Voltage Coefficient	± 100 (ppm/V)	1/10 rated voltage for 3 seconds max. then rated voltage for 3 seconds max.
Robustness of Termination	± (1% + 0.05Ω)	Bend of 2 mm for 5 ± 1 seconds


#### Performance Characteristics (cont.)

Test	Test Specifications	Test Conditions (JIS-C 5202)
Resistance to Solvent	1%: $\pm (0.5\% + 0.05\Omega)$ 5%: $\pm (0.5\% + 0.05\Omega)$ Jumper: Max. 0.05Ω after test	The tested resistor should be immersed into isopropyl alcohol of 20 to 25°C for 60 seconds. Then the resistor is left in the room for 48 hours.
Damp Heat with Load	1%: $\pm (1\% + 0.05\Omega)$ 5%: $\pm (2\% + 0.05\Omega)$ Values < 1Ω: $\pm (3\% + 0.1\Omega)$ Jumper: Max. 0.1Ω after test	40 $\pm 2^\circ\text{C}$ , 90%~95% R.H. RCWV or max. working voltage whichever is less for 1000 hours with 1.5 hours "ON" and 0.5 hours "OFF"

Operating temperature range is -55 to +155°C for all sizes except for 01005 size

Operating temperature range for 01005 is -55 to +125°C

#### Power Derating Curve:



# RMCF / RMCP Series

General Purpose Thick Film Standard Power  
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

## Repetitive Pulse Information

(This information is for reference only and is not guaranteed performance.)

If repetitive pulses are applied to resistors, pulse wave form must be less than "Pulse Limiting Voltage", "Pulse Limiting Current" or "Pulse Limiting Wattage" calculated by the formula below.

$$V_p = K\sqrt{P_x R_x T / t}$$

$$I_p = K\sqrt{P / R_x T / t}$$

$$P_p = K^2 x P_x T / t$$

Where:  $V_p$ : Pulse limiting voltage (V)

$I_p$ : Pulse limiting current (A)

$P_p$ : Pulse limiting wattage (W)

$P$ : Power rating (W)


$R$ : Nominal resistance (ohm)

$T$ : Repetitive period (sec)

$t$ : Pulse duration (sec)

$K$ : Coefficient by resistors type (refer to below matrix)

[ $V_r$ : Rated Voltage (V),  $I_r$ : Rated Current (A)]



Note 1: If  $T > 10 \rightarrow T = 10$  (sec),  $T/t > 1000 \rightarrow T/t = 1000$

Note 2: If  $T > 10$  and  $T/t > 1000$ , "Pulse Limiting power (Single pulse) is applied

Note 3: If  $V_p < V_r$  ( $I_p < I_r$  or  $P_p < P$ ),  $V_r$  ( $I_r$ ,  $P$ ) is  $V_p$  ( $I_p$ ,  $P_p$ )

Note 4: Pulse limiting voltage (current, wattage) is applied at less than rated ambient temperature. If ambient temperature is more than the rated temperature (70°C), please decrease power rating according to "Power Derating Curve"

Note 5: Please assure sufficient margin for use period and conditions for "Pulse Limiting Voltage"


Note 6: If the pulse waveform is not square wave, please judge after transform the waveform into square wave according to the "Waveform Transformation to Square Wave".

RMCF Coefficient (K) Matrix


Ohmic Value	K
$R < 10\Omega$	0.50
$10\Omega \leq R < 100\Omega$	0.45
$100\Omega \leq R < 1K\Omega$	0.35
$1K\Omega \leq R < 10K\Omega$	0.25
$10K\Omega \leq R$	0.20

### Waveform Transformation to Square Wave


1. Discharge curve wave with time constant "t" → Square wave




2. Damping oscillation wave with time constant of envelope "t" → Square wave




3. Half-wave rectification wave → Square wave




4. Triangular wave → Square wave



5. Special wave → Square wave



### Recommended Pad Layout



Type/Code	A	B	C	Unit
RMCF01005	0.008 0.20	0.020 0.50	0.008 0.20	inches mm
RMCF0201 RMCP0201	0.012 0.30	0.039 1.00	0.016 0.40	inches mm
RMCF0402 RMCP0402	0.020 0.50	0.059 1.50	0.024 0.60	inches mm
RMCF0603 RMCP0603	0.031 0.80	0.083 2.10	0.035 0.90	inches mm
RMCF0805 RMCP0805	0.047 1.20	0.118 3.00	0.051 1.30	inches mm
RMCF1206 RMCP1206	0.087 2.20	0.165 4.20	0.063 1.60	inches mm
RMCF1210 RMCP1210	0.087 2.20	0.165 4.20	0.110 2.80	inches mm
RMCF2010 RMCP2010	0.138 3.50	0.240 6.10	0.110 2.80	inches mm
RMCF2512 RMCP2512	0.193 4.90	0.315 8.00	0.138 3.50	inches mm

### Recommended Solder Profile

This information is intended as a reference for solder profiles for Stackpole resistive components. These profiles should be compatible with most soldering processes. These are only recommendations. Actual numbers will depend on board density, geometry, packages used, etc., especially those cells labeled with “\*”.

### 100% Matte Tin / RoHS Compliant Terminations

Soldering iron recommended temperatures: 330°C to 350°C with minimum duration. Maximum number of reflow cycles is 3.

#### Wave Soldering


Description	Maximum	Recommended	Minimum
Preheat Time	80 seconds	70 seconds	60 seconds
Temperature Diff.	140°C	120°C	100°C
Solder Temp.	260°C	250°C	240°C
Dwell Time at Max	10 seconds	5 seconds	*
Ramp DN (°C/sec)	N/A	N/A	N/A

Temperature Diff. = Difference between final preheat stage and soldering stage.

#### Convection IR Reflow

Description	Maximum	Recommended	Minimum
Ramp Up (°C/sec)	3°C/sec	2°C/sec	*
Dwell Time > 217°C	150 seconds	90 seconds	60 seconds
Solder Temp.	260°C	245°C	*
Dwell Time at Max.	30 seconds	15 seconds	10 seconds
Ramp DN (°C/sec)	6°C/sec	3°C/sec	*

#### Recommended Resistor Reflow Profile



# RMCF / RMCP Series


General Purpose Thick Film Standard Power  
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions


Packaging (EIA Standard RS-481)

## Reel Specifications



Reel Type	Wa	M	A	B	C	D	Unit
7" reel for 8 mm tape	$0.354 \pm 0.020$ $9.00 \pm 0.50$	$7.008 \pm 0.079$ $178.00 \pm 2.00$	$0.079 \pm 0.020$ $2.00 \pm 0.50$	$0.531 \pm 0.020$ $13.50 \pm 0.50$	$0.827 \pm 0.020$ $21.00 \pm 0.50$	$2.362 \pm 0.039$ $60.00 \pm 1.00$	inches mm
10" reel for 8 mm tape	$0.394 \pm 0.020$ $10.00 \pm 0.50$	$10.000 \pm 0.079$ $254.00 \pm 2.00$	$0.079 \pm 0.020$ $2.00 \pm 0.50$	$0.531 \pm 0.020$ $13.50 \pm 0.50$	$0.827 \pm 0.020$ $21.00 \pm 0.50$	$3.937 \pm 0.039$ $100.00 \pm 1.00$	inches mm

## Packaging Specifications - Paper Tape (sizes 01005 - 1210)



Type/Code	Nominal Typical Full Reel Weight (g)	Tape Width	A	B	W	E	Unit
RMCF01005	127.3	0.315 8.00	$0.009 \pm 0.002$ $0.24 \pm 0.05$	$0.018 \pm 0.004$ $0.45 \pm 0.10$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF0201 RMCP0201	97.2	0.315 8.00	$0.016 \pm 0.006$ $0.40 \pm 0.15$	$0.028 \pm 0.006$ $0.70 \pm 0.15$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF0402 RMCP0402	94.5	0.315 8.00	$0.028 \pm 0.006$ $0.70 \pm 0.15$	$0.047 \pm 0.006$ $1.20 \pm 0.15$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF0603 RMCP0603	118.3	0.315 8.00	$0.041 \pm 0.008$ $1.05 \pm 0.20$	$0.071 \pm 0.008$ $1.80 \pm 0.20$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF0805 RMCP0805	139.2	0.315 8.00	$0.063 \pm 0.010$ $1.60 \pm 0.25$	$0.093 \pm 0.010$ $2.35 \pm 0.25$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF1206 RMCP1206	151.4	0.315 8.00	$0.077 \pm 0.010$ $1.95 \pm 0.25$	$0.140 \pm 0.010$ $3.55 \pm 0.25$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm
RMCF1210 RMCP1210	175.7	0.315 8.00	$0.110 \pm 0.010$ $2.80 \pm 0.25$	$0.138 \pm 0.008$ $3.50 \pm 0.20$	$0.315 \pm 0.008$ $8.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	inches mm

# RMCF / RMCP Series

General Purpose Thick Film Standard Power  
and High-Power Chip Resistor


Stackpole Electronics, Inc.

Resistive Product Solutions


## Packaging Specifications - Paper Tape (sizes 01005 - 1210)

Type/Code	F	T	P	P0	P1	DØ	Unit
RMCF01005	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.016 \pm 0.004$ $0.40 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF0201 RMCP0201	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.015 \pm 0.006$ $0.38 \pm 0.15$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF0402 RMCP0402	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.016 \pm 0.008$ $0.40 \pm 0.20$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF0603 RMCP0603	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.024 \pm 0.004$ $0.60 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF0805 RMCP0805	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.030 \pm 0.004$ $0.75 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF1206 RMCP1206	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.030 \pm 0.004$ $0.75 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm
RMCF1210 RMCP1210	$0.138 \pm 0.002$ $3.50 \pm 0.05$	$0.030 \pm 0.004$ $0.75 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.004$ $2.00 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	inches mm

## Packaging Specifications - Plastic Tape (sizes 2010 and 2512)



Type/Code	Nominal Typical Full Reel Weight (g)	Tape Width	A	B	W	E	F	Unit
RMCF2010 RMCP2010	183.1	0.472 12.00	$0.110 \pm 0.008$ $2.80 \pm 0.20$	$0.217 \pm 0.012$ $5.50 \pm 0.30$	$0.472 \pm 0.008$ $12.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	$0.217 \pm 0.002$ $5.50 \pm 0.05$	inches mm
RMCF2512 RMCP2512	255.3	0.472 12.00	$0.134 \pm 0.008$ $3.40 \pm 0.20$	$0.264 \pm 0.008$ $6.70 \pm 0.20$	$0.472 \pm 0.008$ $12.00 \pm 0.20$	$0.069 \pm 0.004$ $1.75 \pm 0.10$	$0.217 \pm 0.002$ $5.50 \pm 0.05$	inches mm
Type/Code	G	H	T	ØD	ØD1	T1	P	Unit
RMCF2010 RMCP2010	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.002$ $2.00 \pm 0.05$	$0.009 \pm 0.004$ $0.23 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	$0.059 \pm 0.004$ $1.50 \pm 0.10$	$0.035 \pm 0.008$ $0.90 \pm 0.20$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	inches mm
RMCF2512 RMCP2512	$0.157 \pm 0.004$ $4.00 \pm 0.10$	$0.079 \pm 0.002$ $2.00 \pm 0.05$	$0.009 \pm 0.004$ $0.23 \pm 0.10$	$0.059 +0.004/-0$ $1.50 +0.10/-0$	$0.059 \pm 0.004$ $1.50 \pm 0.10$	$0.035 \pm 0.008$ $0.90 \pm 0.20$	$0.157 \pm 0.004$ $4.00 \pm 0.10$	inches mm



The data provided are for reference only. They are typical performance for this product but are not guaranteed. The actual pulse handling of each individual resistor may vary depending on a variety of factors including resistance tolerance and resistance value. Stackpole Electronics, Inc. assumes no liability for the use of this information. Customers should validate the performance of these products in their applications. Contact Stackpole Marketing at [marketing@seiselect.com](mailto:marketing@seiselect.com) to discuss specific pulse application requirements.

### Temperature Measurement of Resistor Surface


Description: The resistor surface generated temperature variation after applied rated voltage.

Size	0201	0402	0603	0805	1206	1210	2010	2512
R-V	15K	40.2K	57.6K	180K	182K	100K	100K	75K
Rated Power (W)	1/20	1/16	1/10	1/8	1/4	1/2	3/4	1
Max Rated Voltage (V)	25	50	75	150	200	200	200	200

Test method: Measure component surface temperature directly after the temperature stabilizes.

Test result: As per table below:

### Hot Spot Temperature - RMCF



Size	0201	0402	0603	0805	1206	1210	2010	2512
Surface Temp. (°C)	36	37	46.2	50.4	70.6	110.6	141	150.4

The thermal resistance of the RMCP will be similar to the RMCF. For example, the RMCF2512 and the RMCP2512 will have similar surface temperatures at 1W; the RMCP is designed to withstand higher temperatures associated with high power levels.

# RMCF / RMCP Series

General Purpose Thick Film Standard Power  
and High-Power Chip Resistor

Stackpole Electronics, Inc.

Resistive Product Solutions

## Part Marking Instructions

### E96 and E24 Values for 0805-2512 (1% tolerances)

The nominal resistance is marked on the surface of the overcoating with the use of  
**four character markings.**

1. Values  $< 100\Omega$  will use "R" as the decimal holder.

1R21  
1.21Ω

1000  
100Ω

### E24 Values for 0805-2512 (5% tolerance, $\leq 0.91\Omega$ )

The nominal resistance is marked on the surface of the overcoating with the use of  
**four character markings.**

1. Values  $\leq 0.91\Omega$  will use "R" as the decimal holder.

R680  
0.68Ω

### E24 Values for 0805-2512 (5% tolerance, $\geq 1\Omega$ )

The nominal resistance is marked on the surface of the overcoating with the use of  
**three character markings.**

1. Values between  $1\Omega$  and  $9.1\Omega$  will use "R" as the decimal holder.

1R0  
1Ω  
122  
1.2 KΩ

### E24 Values for 0603

The nominal resistance is marked on the surface of the overcoating with the use of  
**three character markings.**

1. Values between  $0.1\Omega$  and  $9.1\Omega$  will use "R" as the decimal holder.

R68  
0.68Ω 5%  
100  
10Ω 5%  
221  
220Ω 1%

2. Values  $\geq 10\Omega$  will use no decimal holder.

3. 5% tolerance is not underlined. 1% tolerance is underlined.

(Effective date for 1% underline marking is date codes on/or after April 1<sup>st</sup>, 2025)

4. Values that are both E24 and E96 follow E96 marking rules.

### E96 Values for 0603 size (1% tolerances)

A two character number is assigned to each standard R-Value (E96) as shown in  
the chart below. This is followed by one alpha character which is used as a  
multiplier. Each letter from "Y" - "F" represents a specific multiplier.

03X  
10.5Ω

Alpha Character = Multiplier	
Y = 0.1	C = 1000
X = 1	D = 10000
A = 10	E = 100000
B = 100	F = 1000000

Chip Marking	Value
01B =	$10.0 \times 100 = 1\text{ K}\Omega$
25C =	$17.8 \times 1000 = 17.8\text{ K}\Omega$
93D =	$90.9 \times 10000 = 909\text{ K}\Omega$

### E96

#	R-Value										
01	10.0	17	14.7	33	21.5	49	31.6	65	46.4	81	68.1
02	10.2	18	15.0	34	22.1	50	32.4	66	47.5	82	69.8
03	10.5	19	15.4	35	22.6	51	33.2	67	48.7	83	71.5
04	10.7	20	15.8	36	23.2	52	34.0	68	49.9	84	73.2
05	11.0	21	16.2	37	23.7	53	34.8	69	51.1	85	75.0
06	11.3	22	16.5	38	24.3	54	35.7	70	52.3	86	76.8
07	11.5	23	16.9	39	24.9	55	36.5	71	53.6	87	78.7
08	11.8	24	17.4	40	25.5	56	37.4	72	54.9	88	80.6
09	12.1	25	17.8	41	26.1	57	38.3	73	56.2	89	82.5
10	12.4	26	18.2	42	26.7	58	39.2	74	57.6	90	84.5
11	12.7	27	18.7	43	27.4	59	40.2	75	59.0	91	86.6
12	13.0	28	19.1	44	28.0	60	41.2	76	60.4	92	88.7
13	13.3	29	19.6	45	28.7	61	42.2	77	61.9	93	90.9
14	13.7	30	20.0	46	29.4	62	43.2	78	63.4	94	93.1
15	14.0	31	20.5	47	30.1	63	44.2	79	64.9	95	95.3
16	14.3	32	21.0	48	30.9	64	45.3	80	66.5	96	97.6

Note: 01005, 0201, and 0402 sizes are unmarked.

### RoHS Compliance

Stackpole Electronics has joined the worldwide effort to reduce the amount of lead in electronic components and to meet the various regulatory requirements now prevalent, such as the European Union's directive regarding "Restrictions on Hazardous Substances" (RoHS 3). As part of this ongoing program, we periodically update this document with the status regarding the availability of our compliant components. All our standard part numbers are compliant to EU Directive 2011/65/EU of the European Parliament as amended by Directive (EU) 2015/863/EU as regards the list of restricted substances.

RoHS Compliance Status						
Standard Product Series	Description	Package / Termination Type	Standard Series RoHS Compliant	Lead-Free Termination Composition	Lead-Free Mfg. Effective Date (Std Product Series)	Lead-Free Effective Date Code (YY/WW)
RMCF	General Purpose Thick Film Standard Power Chip Resistor	SMD	YES <sup>(1)</sup>	100% Matte Sn over Ni	Jan-04 (Japan) Jan-05 (Taiwan, China)	04/01 05/01
RMCP	General Purpose Thick Film High-Power Chip Resistor	SMD	YES <sup>(1)</sup>	100% Matte Sn over Ni	Always	Always

Note (1): RoHS compliant by means of exemption 7c-l.

### "Conflict Metals" Commitment

We at Stackpole Electronics, Inc. are joined with our industry in opposing the use of metals mined in the "conflict region" of the eastern Democratic Republic of the Congo (DRC) in our products. Recognizing that the supply chain for metals used in the electronics industry is very complex, we work closely with our own suppliers to verify to the extent possible that the materials and products we supply do not contain metals sourced from this conflict region. As such, we are in compliance with the requirements of Dodd-Frank Act regarding Conflict Minerals.


### Compliance to "REACH"

We certify that all passive components supplied by Stackpole Electronics, Inc. are SVHC (Substances of Very High Concern) free and compliant with the requirements of EU Directive 1907/2006/EC, "The Registration, Evaluation, Authorization and Restriction of Chemicals", otherwise referred to as REACH. Contact us for complete list of REACH Substance Candidate List.

### Environmental Policy

It is the policy of Stackpole Electronics, Inc. (SEI) to protect the environment in all localities in which we operate. We continually strive to improve our effect on the environment. We observe all applicable laws and regulations regarding the protection of our environment and all requests related to the environment to which we have agreed. We are committed to the prevention of all forms of pollution.

## How to Order - RMCF



## How to Order - RCMP

