



Micrometer with dial comparator, Measuring range: 0-25mm



Order data

Order number	422510 0-25
GTIN	4045197203991
Item class	42B

Description

Version:

Measuring spindle through-hardened and ground. With fine-lapped **carbide measuring faces**. Spindle and anvil made of stainless steel. One piece frame and spindle guide. Button for retracting the measurement anvil for repetitive measurements. With adjustment screw for zeroing. Tolerance pointers for good/ reject measurements. With hand temperature protection. Lever for spindle clamping.

Callout:

Deviation read-off in 1/1000 mm.
Push button for anvil retraction.

Accuracy:

Precision dial comparator 1 μm – micrometer measurement deviation E MPE $\pm 2 \mu\text{m}$.

Supplied with:

Adjustment wrench.

Technical description

Measuring range dial comparator	$\pm 0.045 \text{ mm}$
Graduation of the micrometer	0.01 mm
Graduation of the precision dial comparator	0.001 mm
Measuring range	0 - 25 mm
Clearance depth of micrometer frame	18 mm
Standard	ISO 3611

Micrometer barrel graduations	1/50 mm
Measurement technology	analogue
Packaging	sturdy box
Calibration	B9
Type of product	Micrometer with dial comparator

Suitable products

<https://www.hoffmann-group.com/GB/en/hom/p/422510-0-25>